

NEW

Gas spring 3/8



Facts:

- **Diameter:** 3/8 mm
- **Force F1:** 7 - 110 N
- **Stroke:** 10 - 120 mm
- **Extended length:** 2x stroke + 30 mm

- **Progressivity:** 28 %

- **CeramPro® Piston rod, highly corrosion resistant**

A piston rod diameter of 3 mm and a cylinder diameter of 8 mm allow a **very low weight** of the new 3/8 series. Its **small size** is ideal for applications with limited space.

The tested and proven Bansbach sealing package, guarantees **low friction** also in the 3/8 series. Extension forces starting at 7N can be achieved.

The **CeramPro®** surface of the piston rod offers maximal corrosion resistance. This special treatment gives the surface an extremely fine and durable finish with excellent movement.

Let the many connector variations convince you which are offered with this "MINI SERIES". The extensive Easylift system can satisfy almost any mounting requirement.

The flyer is subject to technical alterations and printing mistakes. Technische Änderungen und Druckfehler vorbehalten.

Bansbach easylift GmbH
Barbarossastraße 8
D-73547 Lorch

Tel. +49 (0) 7172/9107-0
Fax +49 (0) 7172/9107-44

info@bansbach.de
www.bansbach.de

Bansbach
easylift